



UL Online Certifications Directory

[Home](#) [Quick Guide](#) [Contact Us](#) [UL.com](#)

PGJI2.MH19500 Printing Materials - Component

[Page Bottom](#)

Printing Materials - Component

[See General Information for Printing Materials - Component](#)

CABLOG

MH19500

ZONE INDUSTRIELLE DES CHAMPS DOLENTS
8, RUE SETUBAL
60000 BEAUVAIS, FRANCE

Label materials suitable for additional printing using one or more of the following inks.

Inks

1 - Advent "AD-501", Armor "AXR-7+", Astro-Med "RD", "RF", "R5", Atech Systems "HS-3", ICS "2000", "2099", "CC-4099", Iimak "SH-36", "SP-330", Intermec "054048-4", "053258-3", "E05733", "E05734", "E05735", "E05736", "E05737", "E05738", "E05739", "E05740", "E07530", "E07531", "E07532", "E07533", "E07534", "E07535", "E07536", Japan Pulp and Paper "JP Resin 1", Japan Pulp and Paper GmbH "Sigma P", NCR "Promark" and "Matrix", Regma "51053", Ricoh "B110-C", RJS "Thermax Q", Sato "Premier 1", Sony "4070", "4072", "4075", United Barcode Industries "HS-3", UBI "HR03", UBI "HR04", Zebra "5175", "5095" "5100" thermal transfer ribbons.

2 - Advent "AD-301", Armor "AXR-7+", NCR "Ultra V", "Pacesetter", Iimak "SH-36", "SP-330", "NET", "NET-BX", "NET-872", Regma "31521", Ricoh "B110-C", "TRX-21", Sato "Premier 1", Sony "4070", "4072", United Barcode Industries UBI "HR03", UBI "HR04", Zebra "5555", "5175", "5586", "5114", "5095" thermal transfer ribbons.

3 - Hitachi "HMT-446" toner or Pentax "Laserfold" toner.

4 - Hewlett Packard "92291A", "92274A", "92275A", "92295A", "92298A", "C3900A", "C3903A", "C3909A" toner.

5 - Kurz "K-300" black, "K-500" black, "K-501" black, "990848 5.7" red, "K-550" red, "990846 5.7" blue, "K-550" green, "K-550" brown, "K-550" white, "K-550" yellow and "990854 A1 5.7" silver thermal transfer ribbons.

6 - Armor "AXR7", ICS-CC "4099-01", Iimak "SH-36", Ricoh "B110A", "B110C", Sony "4070" thermal transfer ribbons.

7 - Nitto Denko "Duraink SA" thermal transfer ribbon.

8 - Armor "AXR7", Dai Nippon "R510" thermal transfer ribbons.

Pressure-sensitive systems:

Model Dsg.	Application Surface	Max Temp (C)	Min Temp (C)	Indoor Use	Outdoor Use	Additional Conditions
Gold polyamide.						
Printed label dsg: C450 Inks: 7						
	Aluminum (AL)	175	-29	X	-	-
	Glass	175	-29	X	-	-
	Stainless steel (SS)	175	-29	X	-	-
	Gass impregnated epoxy resin	150	-29	X	-	-
	Nylon - polyamide (PA)	100	-29	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-29	X	-	-
	Polycarbonate (PC)	100	-29	X	-	-
	Polypropylene (PP)	80	-29	X	-	-
Silver polyester.						
Unprinted stock dsg: C420M-v Printed label dsg: C420M Inks: 2, 3						
	Alkyd paint (AK PT)	150	-29	X	-	-
	Aluminum (AL)	150	-29	X	-	-
	Galvanized steel (GS)	150	-29	X	-	-
	Stainless steel (SS)	150	-29	X	-	-
	Polyester paint (PER PT)	125	-29	X	-	-
	Melamine (ME)	100	-29	X	-	-
	Nylon - polyamide (PA)	100	-29	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-29	X	-	-
	Polycarbonate (PC)	100	-29	X	-	-
	Polypropylene (PP)	80	-	X	-	-
	Polystyrene (PS)	80	-29	X	-	-
	Unsaturated polyester - thermoset (UP)	80	-29	X	-	-
	Acrylonitrile butadiene styrene (ABS)	60	-29	X	-	-
Unprinted stock dsg: C620-v Printed label dsg: C620 Inks: 1, 5						

	Alkyd paint (AK PT)	150	-40	X	-	-
	Aluminum (AL)	150	-40	X	-	-
	Galvanized steel (GS)	150	-40	X	-	-
	Stainless steel (SS)	150	-29	X	-	-
	Polyester paint (PER PT)	125	-29	X	-	-
	Melamine (ME)	100	-29	X	-	-
	Nylon - polyamide (PA)	100	-29	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-29	X	-	-
	Polycarbonate (PC)	100	-29	X	-	-
	Porcelain (PRCLN)	100	-40	X	-	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	-
	Polypropylene (PP)	80	-	X	-	-
	Polystyrene (PS)	80	-29	X	-	-
	Unsaturated polyester - thermoset (UP)	80	-40	X	-	-

White acrylic.

Unprinted stock dsg: **C480-v**

Printed label dsg: **C480**

Inks: 6

	Acrylic paint (AC PT)	175	-40	X	-	-
	Anodized aluminum	175	-40	X	-	-
	Galvanized steel (GS)	175	-40	X	-	-
	Polyester paint (PER PT)	175	-40	X	-	-
	Porcelain (PRCLN)	175	-40	X	-	-
	Stainless steel (SS)	175	-40	X	-	-
	Nylon - polyamide (PA)	100	-	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
	Polycarbonate (PC)	100	-40	X	-	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	-
	Polyphenylene oxide/ether (PPOX)	80	-40	X	-	-
	Polypropylene (PP)	80	-	X	-	-
	Polystyrene (PS)	80	-40	X	-	-

White and silver polyester.

Unprinted stock dsg: **C410T-v, C420-v**

Printed label dsg: **C410T, C420**

Inks: 2, 5

	Acrylic paint (AC PT)	150	-40	X	-	-
	Alkyd paint (AK PT)	150	-40	X	-	-
	Aluminum (AL)	150	-40	X	-	-
	Galvanized steel (GS)	150	-40	X	-	-
	Polyester paint (PER PT)	150	-29	X	-	-
	Porcelain (PRCLN)	150	-29	X	-	-
	Stainless steel (SS)	150	-29	X	-	-
	Melamine (ME)	100	-29	X	-	-
	Nylon - polyamide (PA)	100	-29	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-29	X	-	-
	Polycarbonate (PC)	100	-29	X	-	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	-
	Polypropylene (PP)	80	-	X	-	-
	Polystyrene (PS)	80	-29	X	-	-
	Unsaturated polyester - thermoset (UP)	80	-40	X	-	-

White polyester.

Unprinted stock dsg: **C410M-v**

Printed label dsg: **C410M**

Inks: 2, 4

	Acrylic paint (AC PT)	150	-29	X	-	-
	Alkyd paint (AK PT)	150	-29	X	-	-
	Aluminum (AL)	150	-29	X	-	-
	Galvanized steel (GS)	150	-29	X	-	-
	Polyester paint (PER PT)	150	-29	X	-	-
	Porcelain (PRCLN)	150	-29	X	-	-
	Stainless steel (SS)	150	-29	X	-	-
	Melamine (ME)	100	-29	X	-	-
	Nylon - polyamide (PA)	100	-29	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-29	X	-	-
	Polycarbonate (PC)	100	-29	X	-	-
	Polypropylene (PP)	80	-	X	-	-

	Polystyrene (PS)	80	-29	X	-	-
	Unsaturated polyester - thermoset (UP)	80	-29	X	-	-
	Acrylonitrile butadiene styrene (ABS)	60	-29	X	-	-

Unprinted stock dsg: **C610-v**

Printed label dsg: **C610**

Inks: 1, 5

	Acrylic paint (AC PT)	150	-40	X	-	-
	Alkyd paint (AK PT)	150	-40	X	-	-
	Aluminum (AL)	150	-40	X	-	-
	Galvanized steel (GS)	150	-40	X	-	-
	Polyester paint (PER PT)	150	-29	X	-	-
	Porcelain (PRCLN)	150	-29	X	-	-
	Stainless steel (SS)	150	-29	X	-	-
	Melamine (ME)	100	-29	X	-	-
	Nylon - polyamide (PA)	100	-29	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-29	X	-	-
	Polycarbonate (PC)	100	-29	X	-	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	-
	Polypropylene (PP)	80	-	X	-	-
	Polystyrene (PS)	80	-29	X	-	-
	Unsaturated polyester - thermoset (UP)	80	-40	X	-	-

White Polyimide.


Unprinted stock dsg: **C450b-v**

Printed label dsg: **C450b**

Inks: 8

	Alkyd paint (AK PT)	175	-10	X	-	-
	Aluminum (AL)	175	-29	X	-	-
	Galvanized steel (GS)	175	-10	X	-	-
	Glass	175	-29	X	-	-
	Stainless steel (SS)	175	-29	X	-	-
	Epoxy (EP)	150	-29	X	-	-
	Nylon - polyamide (PA)	100	-29	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-29	X	-	-

	Polycarbonate (PC)	100	-29	X	-	-
--	--------------------	-----	-----	---	---	---

Marking: Company name, product designation and the Recognized Component Mark,  on packages of stock. Company name and ink designation on packages of ink.

[Last Updated](#) on 2008-07-24

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".